Roll No .....

## **CE-7002 (CBGS)**

## **B.E. VII Semester**

Examination, November 2019


## Choice Based Grading System (CBGS) Structural Design -II (Steel)


Time: Three Hours

Maximum Marks: 70

Note: i) Attempt any five questions.

- ii) All questions carry equal marks.
- iii) Use of relevant IS code is permitted.
- A welded bracket connects a plate to the column flange as shown in figure. Determine the size of the weld if the allowable stress in the weld is 110 N/mm<sup>2</sup>.





Take  $Fy = 250 \text{ N/mm}^2$ .

3. Explain the steps involved in the design of gantry girder. 14

- 4. Design a column section to support a load of 1000 kN. The section shall consists of four angles. The overall dimensions of the section shall be 250 mm × 250 mm. The column has an effective length of 4m. Take Fy = 250 MPa.
- Draw the schematic diagram showing various components of braced industrial building.
- Design a slab base for a column ISHB 300 @ 577 N/m carrying an axial load of 1200 kN. M20 concrete is to be used for the foundation. Provide welded connection between the column and base plate.



- 7. a) Tensile strength is of secondary importance in most of steel structure. State True or False. Support your answer.
  - b) What do you mean by formation of plastic Hinge in beams.

- a) What are the reasons for the failure of riveted joints?
   Explain briefly.
  - b) Design a lap joint for connection two plates of sizes 15cm × 1cm and 20cm × 1cm allowing a safe shear stress of 1025 kg/cm² in the weld. Permissible tensile stress in the plate = 1500 kg/cm².



\*\*\*\*